



UP50H – Compact Lab Homogenizer

www.hielscher.com/up50

<p>Ultrasonic Lab Device UP50H</p>	 <p>UP50H - compact light-weight ultrasonic device</p>	 <p>UP50H at stand ST1-16</p>
<p>Technical Details</p>	<p>UP50H: Compact ultrasonic lab device (50W, 30kHz) for handheld and stand-mounted operation, automatic frequency tuning, amplitude adjustable from 20 to 100%, pulse adjustable from 0 to 100%, dry running protected, with 9-pin DSUB interface, light-weight, in portable case, IP40 grade, titanium horn</p>	
<p>Applications</p>	<p>Homogenization, Dispersing & Deagglomeration (e.g. nano particles), Wet-milling, Emulsifying, Lysis & Cell Disintegration, Extraction, Degassing, Sonochemistry</p>	
<p>Advantages</p>	<p>Performance: With 50 watts power, the UP50H is much more powerful than an ultrasonic bath or tank. Flexibility: For handheld or stand-mounted use, with various accessories for optimal adaption to your process. Quality: The UP50H device fullfills the highest quality standards. All devices are designed, engineered and manufactured in Germany.</p>	

Items:

- Ultrasonic Processor UP50H ◦ 115 volts ◦ 230 volts
- Sonotrode MS3 (tip diameter 3mm)
- Sonotrode MS14 (tip diameter 7mm)
- Stand ST1-16
- ST1-Clamp
- PowerMeter PowMet ◦ 115 volts ◦ 230 volts