



C-MAG MS 4 IKAMAG®

New magnetic stirrer without heating. With ceramic set-up plate which offers excellent chemical resistance.

- Powerful motor for stirring quantities of up to 5 l (H₂O)
- Elevated control panel for protection against leaking liquids

Accessories: IKAFLON® 10 Magnetic stirring bar, IKAFLON® 15 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, RS 1 Set of magnetic stirring bars, RSE Stirring bar remover, H 16 V Support rod

Technical Data

| | |
|---|-----------------|
| Number of stirring positions | 1 |
| Stirring quantity max. per stirring position (H ₂ O) [l] | 5 |
| Stirring quantity max. (H ₂ O) [l] | 5 |
| Motor rating input [W] | 15 |
| Motor rating output [W] | 1.5 |
| Speed display | scale |
| Speed range [1/min] | 100 - 1500 |
| Speed control | scale 0 - 6 |
| Set-up plate material | ceramic |
| Set-up plate dimensions [mm] | 120 x 120 |
| Dimensions (W x H x D) [mm] | 150 x 105 x 260 |
| Weight [kg] | 3 |
| Permissible ambient temperature [°C] | 5 - 40 |
| Permissible relative moisture [%] | 80 |
| Protection class according to DIN EN 60529 | IP 21 |
| Voltage [V] | 230 |
| Frequency [Hz] | 50/60 |
| Power input [W] | 30 |
| Ident. No. | 3582200 |