



KOJAIR®



CLEANWIZARD H

Product Safety Horizontal flow Cabinet

GENERAL

Safe, reliable and economic safety cabinet for protection of the work item including ergonomic practical properties needed in normal work.

TECHNICAL INFORMATION

Materials and finishing

All materials and surfaces are smooth and resistant to cleaning and disinfection agents.

Lighting

Glare-free and shadow-free fluorescent lighting providing illumination on work surface 1200 lux

Standard equipment

- Flow control with digital display
- Alarms for false flow speed
- 1/2 speed via switch
- UV outlet via switch
- Base stand 700, 800 or 900 mm



Filters

HEPA H 14 99,995 % MPPS
acc. to EN 1822

Air speed

Air flow 0,4 m/s ± 20%

Sound level

The sound level with clean filters is 55 dB.

Options

- UV light 30 W
- Gas tap
- Socket

CleanWizard H	130 H	200 H
Total width (mm)	1280	1910
Depth	870	870
Working space (mm)		
Width	1180	1830
Depth	500	500
Height	610	610
Power (max. W)	470	730
Weight (incl. base stand kg)	180	220

Manufacturing Plant and Head Office: Teollisuustie 3, FIN-35700 Vilppula, Finland

MANEKO spol. s r.o., Na Pískách 71, 160 00 Praha 6
tel.: 233 335 638 - 9, 233 336 579, fax: 233 332 656

E-mail: maneko@maneko.cz
www.maneko.cz