

## Precision incubator

### Model IF75plus



## Standard equipment

### Ventilation and Control

- forced air circulation by quiet air turbine, adjustable in 10 % steps for each segment individually
- adjustment of pre-heated fresh air admixture by air flap control in 10 % steps for each segment individually
- vent connection with restrictor flap
- adaptive multifunctional digital PID-microprocessor controller with 2 high-definition TFT-colour displays
- self-diagnostics for fault analysis
- 2 Pt100 sensors Class A in 4-wire-circuit, mutually monitoring and taking over the performance at the same temperature value
- digital timer adjustable from 1 minute to 99 days
- parameters adjustable on ControlCOCKPIT: temperature (Celsius or Fahrenheit), fan speed, air flap position, programme time, time zones, summertime/wintertime
- SetpointWAIT function - the process time does not start until the set temperature is reached
- AtmoCONTROL software on a USB stick for programming, managing and transferring programmes via Ethernet interface or USB port
- HeatBALANCE function for adapting the distribution of the heating performance of the upper and lower heating circuit from -50 % to +50 %
- Setting of languages on ControlCOCKPIT: German/English/Spanish/French
- resolution of display for setpoint and actual temperature values 0.1 °C
- calibration facility directly at ControlCOCKPIT for three freely selectable temperature values
- programme stored in case of power failure
- fixed sterilisation programme (4 hours/160 °C) for sterilisation of working chamber, not for sterilising the load
- incl. works calibration certificate for +37 °C

### Multiple Overtemperature Protection

- with audible and visual alarm
- overtemperature monitor TWW, protection class 3.1 or adjustable temperature limiter TWB, protection class 2, selectable on display
- additionally integrated over- and undertemperature monitor "ASF", automatically following the setpoint value at a preset tolerance range; alarm in case of over-

or undertemperature, heating is switched off in case of overtemperature

- mechanical temperature limiter TB, protection class 1 according to DIN 12 880 to switch off the heating approx. 20 °C above nominal temperature

#### **Textured Stainless Steel Casing**

- w x h x d: 585 x 944 x 514 mm
- fully insulated stainless steel door with 2-point locking (compression door lock)
- inner glass door
- rear zinc-plated steel

#### **Interior - Heating Concept**

- w x h x d: 400 x 560 x 330 mm, 74 l
- easy-to-clean interior, made of stainless steel, reinforced by deep drawn ribbing with integrated and protected large-area heating on four sides
- 2 stainless steel grids
- Max. loading of chamber: 120 kg

#### **Temperature Range**

- min. 10 °C above ambient up to +80 °C

#### **Voltage / Power Rating**

- 230 V (+/- 10 %), 50/60 Hz / approx. 1.250 W
- 115 V (+/- 10 %), 50/60 Hz / approx. 1.100 W

#### **Packing Data**

- net weight approx. 66 kg
- gross weight carton approx. 87 kg
- dimensions approx.:  
carton w x h x d: 73 x 112 x 67 cm
- the appliances must be transported upright

#### **Customs Tariff Number**

- 8419 8998

#### **Country of Origin**

- Federal Republic of Germany

#### **WEEE-Reg.-No.**

- DE 66812464