

## Laboratory Chest Freezer ProfiLine Pollux PLPO

- Static cooling and manual defrost
- Electronic control and digital display
  - Visual/audible alarm warning for excess and insufficient temperature
  - No-volt remote alarm contact for connection to a remote alarm system
- External housing made of white, galvanized steel plate
- Interior made of aluminium
- Condensate drain integrated in base
- Lockable lid and spring-loaded hinges to allow opening at any angle
- Interior lighting (except for ex-version)
- With castors, supplied separately



ProfiLine Pollux 3645WN

Model ProfiLine Pollux	PLPO1345WN	PLPO2245WN	PLPO3045WN	PLPO3645WN	PLPO4245WN
Temperature range	°C: -5/-45				
Content	litres (gross): 130	226	299	358	416
Ext.dimensions (WxDxH)	mm: 725x731x865	1055x731x865	1305x731x865	1505x731x865	1705x731x865
Int.dimensions 1 (WxDxH)	mm: < see sketch >				
Int.dimensions 2 (WxDxH)	mm: < see sketch >				
Height at open top	mm: 1555	1555	1555	1555	1555
Weight	kgs: 43	54	64	67	77
Mains connection	volts/Hz/Ph: 230/50/1				
Insulation CFC-free	mm: 100				
Refrigerant	: R404				

**Alternative units:** ProfiLine Taurus and LabStar Mira.

### ProfiLine Pollux + Accessories:

ProfiLine Pollux PLPO 1345WN  
 ProfiLine Pollux PLPO 2245WN  
 ProfiLine Pollux PLPO 3045WN  
 ProfiLine Pollux PLPO 3645WN  
 ProfiLine Pollux PLPO 4245WN

### Cat. No.

GTPLPO1345WN  
 GTPLPO2245WN  
 GTPLPO3045WN  
 GTPLPO3645WN  
 GTPLPO4245WN

ProfiTec Temperature Monitoring and Recording System (see sep. brochure).

GPTEC4A

ProfiCaller telephone dialler (see sep. brochure).

ZXX2-009-TX

Pt-100 temperature sensor, add. installed for ext. temperature recording.

ZXX2-020-2L

Ex-Version „Interior free of ignition sources.“

on request

Storage basket 253x410x183 mm (WxDxH).

ZXX4-092

MIN/MAX thermometer to be placed in refrigerators or freezers.

ZXX2-019-001

Measuring range -50/+50°C, an add. temperature sensor is not required.

MIN/MAX digital thermometer. Hand-held unit with digital display as well as data-hold and relative measuring function. Measuring range -200/+1370°C.


ZXX2-019-011

An add. temperature sensor is required, eg. Cat.-No. ZXX2-022-100.


Temperature sensor for MIN/MAX thermometer ZXX2-019-011.

ZXX2-022-100

Measuring range -100/+1000°C. Length 2 m. Other ranges on request.




### Front view



### Inventory Systems

Stainless steel vertical racks, freezer cassettes and grid inserts enable specimens to be stored and retrieved in a clear and orderly manner. Optimum use is made of the storage capacity. Storage systems are also available for this model in our separate brochures. You can also contact us for a personal consultation.



<http://www.catalopedia.de>

National Lab GmbH  
 Gimbeker Weg 157  
 D-23879 Mölln  
 Tel.: +49 45 42 / 84 91 - 70  
 Fax: +49 45 42 / 84 91 - 71  
 e-Mail: LabSales@NationalLab.com