

## testo 174H

## Mini humidity/temperature logger

The mini data logger testo 174H monitors building climate, continuously, securely and unobtrusively.

- Low-budget temperature and humidity monitoring for living, work, and storage rooms
- Easy readout of the data, and transfer to a PC via Testo USB interface



Actual size

testo 174H, 2-channel temperature and humidity data logger with internal sensor (NTC/capacitive humidity sensor), incl. wall holder, batteries and calibration protocol

Part no.

**0572 6560**

Technical data			
<b>Sensor</b>	<b>NTC/ capacitive humidity sensor</b>	Dimensions	60 x 38 x 18,5 mm
Channels	2 x internal	Battery type	2 x CR 2032 Lithium
Measurement units	°C, °F, %rF, %RH	Protection class	IP20
Measuring range	-20 to +70 °C internal 0 to 100 %RH	Meas. cycle	1 min - 24 h
Accuracy	±0,5 °C (-20 to +70 °C) ±3 %RH (2 to 98 %RH) +0,03 %RH/K	Memory	16.000 readings
Resolution	0,1 °C, 0,1 %RH	Software	ComSoft Basic 5 ComSoft Professional 4
Battery life (at +25 °C)	1 year at 15 meas. rate		
Operating temperature	-20 to +70 °C		
Storage temperature	-40 to +70 °C		

Set	Part no.
testo 174H mini data logger set, 2-channel, incl. USB interface for programming and reading out the logger, wall bracket, battery (2 x CR 2032 lithium) and calibration protocol	0572 0566
Accessories	Part no.
testo 174D - USB interface for programming and reading out the loggers testo 174	0572 0500
Battery testo 174 - Lithium button battery CR 2032 for testo 174 (please order two batteries per logger)	0515 0028
Software	
ComSoft Basic 5 - CD ComSoft Basic 5 (if free, registration-mandatory download not wanted)	0572 0580
ComSoft Professional 4 - Pro software incl. data archiving	0554 1704
Calibration Certificates	
ISO temperature calibration certificate; temperature probe; calibration points: -18 °C, 0 °C, +40 °C; per channel/instrument	0520 0153
ISO humidity calibration certificate; humidity probe; calibration points: 11.3 %RH and 75.3 %RH at +25 °C/+77 °F; per channel/instrument	0520 0076

MANEKO, spol. s r. o.  
 Na pískách 71  
 16000 Praha 6  
 www.maneke.cz  
 maneko@maneko.cz  
 tel: 23333 5638  
 23333 5639, 23333 6645,  
 fax: 23333 2656