

lab dancer vario



- New test tube shaker with touch function. Specially for mixing small sample volumes.
- The lab dancer can be used with all small vessels of up to 30 mm in diameter, e. g. test tubes, centrifuge tubes, Eppendorf vessels
 - Excellent mixing action
 - The upper casing and the test tube surface are made from inert plastic, coated zinc die cast base
 - Speed can be set from 1.000 - 2.800 min⁻¹
 - Includes light 12 V power pack set

Technical Data			
Type of movement [-]	orbital	Orbital diameter [mm]	4.5
Permissible shaking weight (incl. attachment) [kg]	0.1	Motor rating input [W]	1.2
Motor rating output [W]	0.8	Permissible ON time [%]	100
Speed min (adjustable) [1/min]	1000	Speed max. [1/min]	2800
Speed display [-]	none	Timer [-]	no
Timer display [-]	none	Touch function [-]	yes
Shaking table lock [-]	no	Working with microtiter plates [-]	no
Dimensions (W x H x D) [mm]	95 x 70 x 110	Weight [kg]	0.55
Permissible ambient temperature [°C]	5 - 40	Permissible relative moisture [%]	80
Protection class according to DIN EN 60529 [-]	IP 40	Voltage [V]	100 - 240
Frequency [Hz]	50/60	Power input [W]	30