



Vertical autoclaves LVSA 40/60, 50/70, 60/80

for the sterilization of solids and liquids

Specification:

- Cover lock according to pressure vessel regulation TRB
- Absolutely safe and easy to operate
- Automatic programme flow via SPS, display with foil keyboard
- For applications in the medical and microbiological laboratory
- For the sterilization of waste, nutrient media, glassware etc..
- Charging height only 79cm (LVSA 40/60)



LVSA 50/70



LVSA 40/60

Options

- Quick recooling system (double jacket)
- Support pressure regulation for liquids
- Integrated steam generator and vacuum pump set
- Exhaust air filtration with inline-sterilization
- Different baskets (custom-made)
- Process documentation with printer
- Connection to steam network without extra charge
- Extension of the chamber height up to 900mm for fermenters

model	volume	interior space	overall size (wxhxd)	weight	heating	electricity
LVSA 40/60 E	89 litre	Æ 400 x 650 mm	750 x 770 x 600 mm	120 kg	6,6 kW	400V / 16A
LVSA 50/70 E	153 litre	Æ 500 x 715 mm	1050 x 890 x 750 mm	135 kg	6,6 kW	400V / 16A
LVSA 60/80 E	254 litre	Æ 600 x 850 mm	1150 x 1050 x 850 mm	200 kg	9 kW	400V / 16A

