SONOSHAKE

NEW

The new generation: Ultrasonic bath SONOREX DIGITEC DT 1028 F combined with shaking device SA 1028

Ultrasonic bath DT 1028 F + shaking device SA 1028
= SONOSHAKE

Code No: 3257

SONOREX DIGITEC DT 1028 F

- ⇨ especially for sonication of samples in laboratory flasks and for fast degassing
- ⇨ flat ultrasonic bath with a stainless steel tank, inner dimensions 500 × 300 × 65 mm (l × w × d)
- ⇨ housing made of stainless steel, protected against spray, 535 x 325 x 205 mm (l × w × h)
- ⇨ outlet: ball valvue G ½
- ⇨ ultrasonic peak output 1280 W
- ⇨ HF output 320 W
- ⇨ working frequency 35 kHz
- ⇨ Current consumption 1,4 A

SA 1028

- ⇨ analogue setting of time and shaking frequency
- ⇨ reciprocating motion: settings in 4 steps possible of up to 200/min
- ⇨ constant amplitude of 20 mm independently of loading
- ⇨ rack easy to remove – easy mounting of the laboratory clamps EK 10 –100 (separately to order)
- ⇨ floor space approx. 410 x 280 mm (l × w)
- ⇨ mounting of 36 × 10-ml-flasks or 36 × 25-ml-flasks or 18 × 50-ml-flasks or 12 × 100-ml-flasks

- ⇨ required floor space of SONOSHAKE approx. 850 x 360 mm (l × w)

The SONOSHAKE can be used either separately as an ultrasonic bath for sample preparation, a shaking device **SA 1028** only, or both combined!

Code No.: 3249

SA 1028 attachable to existing SONOREX DIGITEC DT 1028 F

BANDELIN
www.bandelin.com
info@bandelin.com

60 years of experience in ultrasound technology
Certification
EN ISO 9001 / 12.2000 • EN ISO 13485:2003 + AC:2007

BANDELIN electronic GmbH & Co. KG
Heinrichstraße 3 – 4 • D-12207 Berlin
Tel.: +49-30-768 80 - 0
Fax: +49-30-773 46 99